TOSHIBA

BV410D BV420D

Desktop printer series

Product brochure

- Toshiba's most advanced desktop print technology was incorporated into the sleekest case design for ultimate user experience.
- Coming with a new powerful and scalable system architecture the BV400D series future-prooves your investment.
- With a broad set of standard interfaces and optional Wi-Fi or Bluetooth, the BV400D series easily integrates into even the most complex IT environments.





The ever-changing workplace

Delivering reliability to meet future challenges

Every business is unique. That's why Toshiba offers the most reliable print solutions that meet all your labelling requirements, day after day. Toshiba barcode printers provide connectivity and solutions to adapt to the needs of an ever-changing workplace.

To shiba's barcode printers continue to deliver on our promise of Together Information – our commitment to collaborate with clients to provide tailored, cost-effective solutions that meet your evolving workplace needs.

The strong combination of excellent design & advanced connectivity

Toshiba's most advanced desktop printer consists of five different models, all with a small footprint, intelligent design which brings simplicity and efficiency raising the user experience the next level. Latest connectivity features enable this printer to be integrated into various networks and, thanks to print language emulations, into almost every print scenario. The robustness of the printer offers high print quality and performance rivalling the majority of mid-ranged printers.



Smooth design yet outstanding

Designed with the user in mind

Ultimate compactness was a core design criteria that led to the creation of the B400D desktop printer range, suitable for versatile applications. With its small footprint and clean case these printers suit retail shops, offices or any workplaces where space is a premium.

Usability clear as day

The sleek design of the BV400D series eliminates all redundant fussiness and concentrates on delivering clarity of operation to the user. The integrated LCD screen of the BV410D provides clear information and notifications that are emphasised by the colour change of the status LEDs. The user can change main settings directly on the printer whereas the remote operator connections allows the full printer setup from afar.

A model to meet every need

With models available in 203 and 300 dpi versions, also available in black or white cabinets, the BV400D series suits to fit into almost any operating environment. With the addition of a linerless version enabling the printer to print on adhesive labels with no backing paper reducing waste and keeping the working environment safe and clean.

Future-ready operating system

The redesigned OS platform supports multi print language emulation, which enables simple integration into complex IT environments. This platform adds not only performance but extends the connectivity and adaptability of the BV400D to keep pace with the requirements of an ever-changing workplace.

Speed & efficiency

A series of features makes sure your desktop printer is ready to print labels and receipts quickly and efficiently at the touch of a button. The BV400D's productivity is maximised by market leading print speeds of up to 7 inches per second and an advanced CPU which processes your data even quicker. Thanks to the rapid boot-time the printer is ready almost instantly at power-on.

Delivering reliability to meet future challenges

Designed to endure the toughest retail environments the renowned reliability of the BV400D printers eliminates almost any downtime – day after day. With optional built-in AC adapters the Toshiba desktop printers are the perfect fit, ensuring a safe work place.

Key highlights

- Market leading throughput with up to 7 ips
- Compact & sleek design with a small footprint
- · Designed, developed & built by Toshiba
- Intuitive & clear user experience
- · Vast print languages & emulations
- Huge performance & functionality at a truly low total cost of ownership



Specifications

Models

White case BV410D-GS02 BV410D-TS02 Resolution 203 dpi (8 dots/mm) 300 dpi (11.8 dots/mm) User Interface 2x LED, 3x key, with LCD 2x LED, 3x keys, with LCD

Resolution 203 dpi (8 dots/mm) 3x LED, 2x key User Interface

Black case linerless cutter BV420D-GL02 Resolution 203 dpi (8 dots/mm) User Interface 3x LED, 2x key Integrated linerless cutter Cutter

General

Direct thermal **Print Method** Printhead Flat head

Dimensions (W x D x H) GS02/TS02 GL02

174 x 218 x 173 mm 174 x 288 x 173 mm

GS02/TS02 Weight 2.0 kg

Memory 128 MB (FROM), 128 MB (SRAM)

Operating Temperature / GS02/TS02

5°-40°C (41°-104°F) / 5°-35°C (41°-95°F) / Humidity 25-85% non-condensing

25-85% non-condensing relative humidity (RH) relative humidity (RH)

Storage Temperature /

-20°-60°C (-40°-140°F) / 10-90% non-condensing relative humidity (RH) Humidity

AC 100-240 V, 50/60 Hz

Power Supply

Print

GS02/TS02 GL02 Sensor Reflective, transmissive Reflective

Max. Print Speed GS02/GL02 TS02 7 ips (177.8 mm/s) 5 ips (127 mm/s)

Max. Print Width GS02/TS02 GL02 108 mm/105.7 mm

Print Length

Batch 8-997 mm Cut 19.4-993 mm¹⁾ Peel-off 23.4-150.4 mm¹⁾

Barcodes UPC/EAN/JAN, Code 39, Code 93, Code 128, EAN 128, NW7, MSI, Interleaved 2 of 5, Industrial 2 of 5, Matrix 2

of 5, POSTNET, RM4SCC, KIX Code, Customer Barcode,

GS1 DataBar, USPS Intelligent Mail Barcode

Data Matrix, PDF 417, MaxiCode, QR Code, 2D Codes

Micro PDF 417, Micro QR, GS1 Data Matrix, Aztec Code

Fonts Bitmap font, outline font, price font, optional TTF,

writable characters

Media

300 dpi (11.8 dots/mm)

3x LED, 2x key

Alignment Centred

Backing Paper Width GS02/TS02 GL02

25.4-118 mm 32-102 mm

Label Thickness 0.06-0.19 mm

Inner Media Core Diameter GS02/TS02 <u>GL02</u> 25.4, 38.1, 42, 76.2 mm 38.1 mm

Outer Media Core Diameter GL02 GS02/TS02

Standard Max. 127 mm Max. 107 mm Optional Max. 214 mm

Media Format Roll, fanfold

Software & Connectivity

Emulation ZPL II, DPL, SBPL

Printer Driver Windows 10/8.1/8/7 (32/64 bit), Windows Server 2016,

Windows Server 2012 R2/Server 2012/Server 2008 R2

SDK

Interface USB 2.0, Ethernet 10/100 Base T (IPv4 & IPv6),

WLAN 802.11a/b/g/n (dual band for 2.4 GHz/5 GHz)¹⁾²⁾, Bluetooth V2.1 EDR with MFi certified¹⁾²⁾, serial port¹⁾

Language Mode TPCL, Basic Command Interpreter (BCI)

BarTender UltraLite (co-packed) **Label Software**

Options

BV410D-GS02/TS02 & BV420D-GS02/TS02

Full cutter module, partial cutter module, peel-off module, serial interface board, wireless LAN module, Bluetooth module, AC adapter cover, external media stand





¹⁾ Optional

²⁾ Availability varies from country to country

About Toshiba Tec

Toshiba Tec UK Imaging Systems Ltd is part of the globally operating Toshiba Tec Corporation, active in various high-tech industrial sectors.

Toshiba Tec Corporation is a leading provider of information technology, operating across multiple industries – ranging from retail, education and business services to hospitality and manufacturing. With headquarters in Japan and over 80 subsidiaries worldwide, Toshiba Tec Corporation helps organisations transform the way they create, record, share, manage and display information.

For more information please contact us:

Toshiba Tec UK Imaging Systems LtdAbbey Cloisters
Abbey Green, Chertsey, KT16 8RB

Telephone 0844 224 4944

Website

www.toshibatec.co.uk

Γ	٦	Together Information is Toshiba's vision for how people and organisations create, record, share, manage and display ideas and data.
		It is based on our belief that the most successful organisations are those that communicate information in the most efficient way.
		We make that possible through an integrated portfolio of industry-specific solutions, all of which reflect Toshiba's commitment to the future of the planet.
L		